

**AMERICAN
TECHNOLOGY**



INVERTER TUBULAR BATTERIES

MORE POWER TO YOU



LOW MAINTENANCE



HIGH POWER



SELENIUM INSIDE



Conditions Apply*

+971 50 7607047

INVERTER TUBULAR BATTERIES

SPECIFICATION CHART

Model Number	Range	Capacity @ At C20 Rate	Warranty (In Months)	Dimensions in {mm}			Charging Current (Amps)
				L	W	H	
TALL TUBULAR XX POWER RANGE							
TP1600TTXX	IT	160	90*	405	192	490	16
TP1800TTXX	IT	180	90*	405	192	490	18
TP2100TTXX	IT	210	90*	405	192	490	21
TP2400TTXX	IT	240	90*	405	192	490	24
TALL TUBULAR X POWER RANGE							
TP1600TTX	IT	160	78*	405	192	490	16
TP1800TTX	IT	180	78*	405	192	490	18
TP2100TTX	IT	210	78*	405	192	490	21
TP2400TTX	IT	240	78*	405	192	490	24
JUMBO TUBULAR XX POWER RANGE							
TP1350JTXX	JUMBO	135	54*	525	267	260	13.5
TP1500JTXX	JUMBO	150	54*	525	267	260	15

Conditions Apply*

PRODUCT FEATURES

- Using best grade PP containers and lid
- Tubular positive plate made with PDC Machine of ZIBO
- High tensile resistance / Porosity polyester gauntlets
- High Porosity PE Envelope separators from DARAMIC, USA
- Micro porous ceramic vent plug
- Heavy duty terminals
- SS fasteners
- Double side pasting negative plate



mena@teslapowerusa.com
www.teslapowerusa.ae

Corporate Office:

Suite #635 S 4000, Hollywood
Blvd Hollywood, Florida,
USA- 33021
Web: www.teslapowerusa.com

MENA Office:

#7, Bel Resheed Building 2
Nad Al Hamar, Deira, Dubai
United Arab Emirates
Web: www.teslapowerusa.ae

APAC Office:

#1003-4-5, Tower-1, DLF
Corporate Greens, Sector 74A,
Gurugram, Haryana-122004
Web: www.teslapowerusa.in